

Mathematics

Advanced GCE

Unit **4730**: Mechanics 3

Mark Scheme for January 2011

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of pupils of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, OCR Nationals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by Examiners. It does not indicate the details of the discussions which took place at an Examiners' meeting before marking commenced.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the Report on the Examination.

OCR will not enter into any discussion or correspondence in connection with this mark scheme.

© OCR 2011

Any enquiries about publications should be addressed to:

OCR Publications
PO Box 5050
Annesley
NOTTINGHAM
NG15 0DL

Telephone: 0870 770 6622
Facsimile: 01223 552610
E-mail: publications@ocr.org.uk

1 i	$(-15\cos\alpha = (0 -) 0.5 \times 22$ or $15\sin\beta = 0.5 \times 22$ Impulse makes angle 42.8° (0.748 rads) with negative x-axis	M1 A1 A1 [3]	M1 for using $I = \Delta(mv)$ in 'x' direction or for sketching Δ reflecting $\mathbf{I} = m(\mathbf{v} - \mathbf{u})$ AEF, but angle must be clear
ii	$15\sin\alpha = 0.5v$ or $15\cos\beta = 0.5v$ or $(0.5v)^2 = 15^2 - 11^2$ Correct explicit expression for v Speed is 20.4 ms^{-1}	M1 A1 A1 [3]	For using $I = \Delta(mv)$ in 'y' direction or using sketched Δ

2	$\frac{1}{2}(m)(v^2 - 6^2) = -(m)g \times 0.5$ in (i) or $\frac{1}{2}(m)(v^2 - 6^2) = -(m)g \times 1$ in (ii) $v^2 = 26.2$ in (i) and 16.4 in (ii) $T = 0.4v^2/0.5$ in (i) or $T + 0.4g = 0.4v^2/0.5$ Tension is 21.0N in (i) (20.96) 9.2N in (ii)	M1 A1 M1 A1 A1 A1 [6]	For using the principle of conservation of energy in (i) or (ii) soi For using Newton's second law with $a = v^2/L$. M1 for either attempt, A1 for both right
---	--	---	--

3 i	$2.8V = 1.4 \times 72$ Vertical component at P is 36 N	M1 A1 [2]	For taking moments about Q for PQ or for using symmetry
ii	$36 + N = 72 + 54$ Normal component at R is 90 N	M1 A1 [2]	For resolving forces vertically on both rods AG
iii	$1.44F = 1.2 \times 90 - 0.8 \times 54$ or $72 \times 1.4 + 54 \times 3.6 + 1.44F = 90 \times 4$ with not more than 1 error in either case Equation correct and leading to $F = 45$ For using $F = \mu R$ Coefficient is 0.5	M1 A1 A1 M1 A1 [5]	For taking moments about Q for QR or about P for the whole structure (all terms needed)

4 i	$0.4(7 \times 0.6) - 0.3 \times 2.8 = 0.4a + 0.3b$ $0.7(7 \times 0.6 + 2.8) = b - a$ Speed of B is 4ms^{-1}	M1 A1 M1 A1 M1 A1 [6]	For using the principle of conservation of momentum For using $e(\Delta u) = \Delta v$ For eliminating a from equations
ii	$a = (-)0.9$ Component perp. to l.o.c. is 5.6 $\tan \alpha = 5.6/0.9$ $\alpha = 80.9^\circ$ Angle turned through is 46.0° (0.803°)	B1 B1 M1 A1 A1ft [5]	 For attempting to find α - the angle between the direction of motion of A after collision and the l.o.c. to the left, or $90^\circ - \alpha$ $126.9^\circ - \alpha$

5 i	$2.45e/0.5 = 0.05g$ $(e = 0.1)$ Distance from O is $0.5 + 0.1 = 0.6\text{m}$	M1 A1 A1 [3]	For using $T = \lambda e/L$ and resolving forces vertically accept use of 0.1 to show both sides equal to 0.49 AG
ii	$mg - T = m\ddot{x}$ $0.05g - 2.45(0.1 + x)/0.5 = 0.05\ddot{x}$ $\ddot{x} = -98x$	M1 A1 A1 [3]	For using Newton's second law with 3 terms AG
iii	$a = 0.075$ $n = 7\sqrt{2}$ oe $x = 0.075\cos(7\sqrt{2}t)$ $x(0.2) = -0.0298$ $v = -0.075(7\sqrt{2})\sin(7\sqrt{2}t)$ $v(0.2) = -0.681 \rightarrow$ velocity is 0.681ms^{-1} upwards	B1 B1 M1 A1 M1 A1ft A1 [7]	accept 9.90 For using $x = a\cos nt$ oe For differentiating $x = a\cos nt$ and using it ft incorrect a and/or n If from $v^2 = n^2(a^2 - x^2)$ the direction must be clearly established

6 i	$112e/4 = 3.5 \times 9.8 \times \frac{40}{49}$ $v^2 = 2 \times 8 \times (4 + 1)$ $v^2 = 80$ $0.5 \sqrt{80} = (0.5 + 3.5)u$ <p>Initial speed of combined particles is</p> $\frac{1}{2} \sqrt{5} \text{ ms}^{-1}$	M1 A1 M1 A1 M1 A1 [6]	For using $mg \sin \theta$ and $\lambda e/L$ For using $s = 4 + e$ and $a = 8$ in $v^2 = 2as$, or by energy For using the principle of conservation of momentum AG
ii	<p>Gain in EE = $(112/(2 \times 4))\{(X+1)^2 - 1^2\}$ Loss of KE = $\frac{1}{2} (0.5 + 3.5) \times 5/4$ Loss of PE = $(0.5 + 3.5) \times 9.8 \times \frac{40}{49} X$</p> $14(X^2 + 2X) = 2.5 + 32X$ $28X^2 - 8X - 5 = 0$	M1 A1 B1 B1 M1 A1 [6]	For using $EE = \lambda x^2/2L$ For using the principle of conservation of energy AG
OR	$T - mg \sin \theta = -ma$ $\frac{112(x+1)}{4} - 4g \frac{40}{49} = -4a$ $\int (7x-1)dx = - \int vdv (+c)$ $\frac{7x^2}{2} - x = -\frac{v^2}{2} + c$ $c = \frac{5}{8}$ $28X^2 - 8X - 5 = 0$	M1 A1 M1 A1 A1 A1 [6]	For use of $F = ma$ allow one sign slip for A1 Using $a = v \frac{dv}{dx}$ and integrating AG Convincingly

7 i	$0.2g - v^2/2000 = 0.2v(dv/dx)$ $\left(\frac{400v}{3920 - v^2}\right) \frac{dv}{dx} = 1.$	M1 A1 [2]	For using Newton's second law with $a = v(dv/dx)$ AG Convincing, with no slips.
ii	$-200 \ln(3920 - v^2) = x + (A)$ $-200 \ln(3920) = A$ $x = 200 \ln\left(\frac{3920}{3920 - v^2}\right)$ $e^{x/200} = 3920/(3920 - v^2)$ $v^2 = 3920(1 - e^{-x/200})$ $0 < e^{-x/200} \rightarrow v^2 < 3920$	M1 A1 M1 A1 M1 A1 B1 [7]	For separating variables and integrating For using $v(0) = 0$ For using inverse ln process AG Convincingly – dep on correct answer
iii	Using $0.2g - v^2/2000 = 0.2a$ $v = 40$ Gain in KE = $\frac{1}{2} 0.2 \times 1600$ (=160J) $x = 200 \ln\left(\frac{3920}{3920 - 1600}\right)$ (= 104.90) $0.2g \times (104.9) - 160$ Work done is 45.6 J	M1 A1 B1ft B1ft M1 A1 [6]	For using WD = loss of PE – gain in KE
OR	Using $0.2g - v^2/2000 = 0.2a$ $v = 40$ $x = 200 \ln\left(\frac{3920}{3920 - 1600}\right)$ (= 104.90...) $WD = \int \frac{v^2}{2000} dx + c$ $= \int \frac{3920}{2000} (1 - e^{-x/200}) dx$ $= 3920 / 2000(x + 200e^{-x/200}) - 392$ Work done is 45.6 J	M1 A1 B1ft M1 A1 A1 [6]	Use of $WD = \int Fdx$ and subst for v^2

OCR (Oxford Cambridge and RSA Examinations)
1 Hills Road
Cambridge
CB1 2EU

OCR Customer Contact Centre

14 – 19 Qualifications (General)

Telephone: 01223 553998

Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

Oxford Cambridge and RSA Examinations
is a Company Limited by Guarantee
Registered in England
Registered Office; 1 Hills Road, Cambridge, CB1 2EU
Registered Company Number: 3484466
OCR is an exempt Charity



OCR (Oxford Cambridge and RSA Examinations)
Head office
Telephone: 01223 552552
Facsimile: 01223 552553

© OCR 2011