

Modified Enlarged 36pt

OXFORD CAMBRIDGE AND RSA EXAMINATIONS

Tuesday 10 June 2025 – Morning

A Level in Design and Technology:
Design Engineering

H404/02 Problem Solving in
Design Engineering

Time allowed: 1 hour 45 minutes
plus your additional time allowance

YOU MUST HAVE:
the Resource Booklet

YOU CAN USE:
a ruler (cm/mm)
a scientific calculator
geometrical instruments

Please write clearly in black ink.

Centre number

--	--	--	--	--

Candidate number

--	--	--	--

First name(s) _____

Last name _____

READ INSTRUCTIONS OVERLEAF



INSTRUCTIONS

Use black ink. You can use an HB pencil, but only for graphs and diagrams.

Write your answer to each question in the space provided. You can use extra paper if you need to, but you must clearly show your candidate number, the centre number and the question numbers.

Answer ALL the questions.

Use the Resource Booklet to answer all the questions.

Where appropriate, your answer should be supported with working. Marks might be given for using a correct method, even if your answer is wrong.

Each question tells you which part of the Resource Booklet to use.

INFORMATION

The total mark for this paper is 70.

The marks for each question are shown in brackets [].

Quality of extended response will be assessed in questions marked with an asterisk (*).

ADVICE

Read each question carefully before you start your answer.

Read the RESOURCE BOOKLET before you answer the questions.

1* The development of autonomous vehicles to help during disasters has introduced many issues for design engineers.

Discuss the key technical challenges AND ethical considerations a design engineer would face when developing an autonomous vehicle for use during disasters.

In your answer you MUST consider:

technical challenges
ethical considerations.

Refer to PAGES 3–9 of the Resource Booklet. [14]

5

6

2* PAGE 7 of the Resource Booklet describes a Magirus Aircore TAF35 fire-fighting robot.

Such complex systems are developed through the collaboration of many different design and engineering specialists.

Critically examine the significance of collaboration amongst engineers in the design and development of complex systems such as the fire-fighting robot.

In your answer you MUST consider:

**the design phase of the product
prototype and testing
manufacture and production.**

Refer to PAGE 7 of the Resource Booklet and also draw on examples from your own studies. [12]

9

10

3 PAGES 10, 11 AND 12 of the Resource Booklet show a concept for a miniature search robot named ‘Scout’.

The Scout robot uses rubber tracks to allow it to travel over uneven ground.

- (a) The rubber tracks are to be purchased from a specialist supplier. The designers need to calculate how much track will be required for the Scout robot.**
- (i) Use FIG. 4 to calculate the length of rubber track that will be needed for ONE side of the Scout robot. Give your answer in mm and show your working. You should ignore track thickness. [3]**

Length of rubber track _____ mm

The design engineers need to calculate the mass of the rubber tracks.

- (ii) Use your answer from PART (a)(i) and FIG. 4 to calculate the total mass of BOTH rubber tracks. Give your answer in kgs and show your working.**

The following equations may prove useful:

(V) Volume = (A) Area $\times$ (L) Length

(m) mass = (ρ) density $\times$ (V) volume [3]

**Total mass of both
rubber tracks _____ kgs**

- (b) It is proposed that each rubber track is driven by an SS-55 electric motor. The drive from the motor will pass through a ZS-50 gear box to the drive sprocket.**

Details of the electric motor and gear box are given on PAGES 13, 14 AND 15 of the Resource Booklet.

- (i) Use FIG. 6 to calculate the velocity ratio of the ZS-50 gear box. Show your working. [2]**

Velocity ratio _____

- (ii) Determine by calculation that the proposed motor gear box combination will produce an output speed of 3.53 km/h for the Scout robot.**

Show your working and use the following information:

**your answer to PART (b)(i)
pages 10, 11, 12 AND 13, 14, 15 of the
Resource Booklet**

**output rotational speed
= $\frac{\text{input rotational speed}}{\text{velocity ratio}}$**

$$v = \frac{3}{25} \pi r N$$

Where:

**v is the speed of the Scout robot
(in km/h)**

**r is the effective radius of the drive
pulley (in m)**

**N is the rotational speed of the drive
pulley (in rpm) [4]**

4 The Scout robot is equipped with a tilting fork mechanism which will help to clear small pieces of debris from its path.

Details of the fork system are shown on PAGES 16 AND 17 of the Resource Booklet.

The forks are actuated using a pneumatic cylinder which is controlled by a programmable control system. The forks are automatically tilted when the system detects an object closer than 150 mm to the robot.

The Scout robot developers have asked you to design the fork actuation system.

There are TWO issues that need to be solved.

Use sketches and/or notes to determine suitable technical solutions that overcome the TWO issues identified.

ISSUE 1:

A pneumatic cylinder must be attached to the forks so that the necessary movement can be achieved.

The forks must lift a 120 N load at their tip as shown in FIG. 7 of the Resource Booklet.

The type of cylinder used is shown in FIG. 8 on PAGE 18 of the Resource Booklet.

1A) Determine the force output of the cylinder and distance of the pivot from the load and effort.

1B) Show a method of attaching the fork to the end of the pneumatic piston to allow for rotary motion at the point of attachment.

ISSUE 2:

The programmable control system uses an ultrasonic sensor to detect objects closer than 150 mm.

When an object is detected, the forks should tilt up.

The forks should return to horizontal when the operator presses a button on the controller.

The system should record the number of times the forks have operated.

Produce a program flow chart for the control system which will achieve the required function. [16]

1A:

1B:

2:

5 The Scout search robot is being designed for batch production.

The manufacturers will make the robot chassis in two parts from 3 mm thick aluminium sheet. They are unsure of the most effective process for manufacture.

Details of the two chassis parts are shown on PAGES 20 AND 21 of the Resource Booklet.

Use sketches and/or notes to show an appropriate method of batch manufacture for the robot chassis.

In your answer you MUST consider:

**a detailed description of the cutting and shaping processes used
details of any dies, formers or jigs
methods of joining the parts to ensure the structural integrity of the completed chassis.**

Refer to PAGES 20 AND 21 of the Resource Booklet. [16]

END OF QUESTION PAPER

Copyright Information

OCR is committed to seeking permission to reproduce all third-party content that it uses in its assessment materials. OCR has attempted to identify and contact all copyright holders whose work is used in this paper. To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced in the OCR Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download from our public website (www.ocr.org.uk) after the live examination series.

If OCR has unwittingly failed to correctly acknowledge or clear any third-party content in this assessment material, OCR will be happy to correct its mistake at the earliest possible opportunity.

For queries or further information please contact The OCR Copyright Team, The Triangle Building, Shaftesbury Road, Cambridge CB2 8EA.

OCR is part of Cambridge University Press & Assessment, which is itself a department of the University of Cambridge.